

Medium wall adhesive-lined polyolefin tubing

中壁含膠熱收縮套管

**ATM****Medium wall adhesive-lined polyolefin tubing****Applications**

Designed with large expansion ratios and an inner liner of hot melt adhesive, which provides excellent insulation and protection to cable joints and terminations, and high impact, abrasion and corrosion resistance for applications in communication cable and chemical pipe.

Characteristics

More flexible than heavy wall tube

Easily fits over irregular shape and large connectors

Resistant to UV and high electrical insulation

Operating temperature range

Operating temperature: -55°C ~ 110°C

Minimum shrink temperature: 80°C

Minimum full recovery temperature: 120°C

order ref. number	diameter		recovered wall	standard
	as supplied (mm)	after recovery (mm)	thickness (mm)	length (mm)
ATM, medium-wall tubing with hot melting adhesive				
ATMø8/2	8	2	1.7	1220
ATMø12/3	12	3	2.0	1220
ATMø16/5	16	5	2.2	1220
ATMø22/6	22	6	2.5	1220
ATMø28/6(11)	28	6	2.5	1220
ATMø33/8(13)	33	8	2.5	1220
ATMø40/12(15)	40	12	2.5	1220
ATMø44/14(17)	44	14	2.5	1220
ATMø55/16(20)	55	16	2.7	1220
ATMø65/19	65	19	2.8	1220
ATMø75/22(27)	75	22	3.0	1220
ATMø85/25	85	25	3.0	1220
ATMø95/25(35)	95	25	3.0	1220
ATMø115/34	115	34	3.0	1220
ATMø140/42(50)	140	42	3.0	1220
ATMø160/50	160	50	3.0	1220
ATMø180/58	180	58	3.5	1220
ATMø200/65	200	65	3.5	1220
ATMø235/65	235	65	3.5	1220
GTM, medium-wall tubing without hot melting adhesive				
GTMø8/2	8	2	1.7	1220
GTMø12/3	12	3	2.0	1220
GTMø16/5	16	5	2.2	1220
GTMø22/6	22	6	2.2	1220
GTMø25/8	25	8	2.3	1220
GTMø33/8	33	8	2.5	1220
GTMø35/12	35	12	2.3	1220
GTMø40/12	40	12	2.5	1220
GTMø40/16	40	16	2.3	1220
GTMø55/16	55	16	2.7	1220
GTMø65/19	65	19	2.8	1220
GTMø75/22	75	22	3.0	1220
GTMø85/25	85	25	3.0	1220
GTMø95/25	95	25	3.0	1220
GTMø115/34	115	34	3.0	1220
GTMø140/42	140	42	3.0	1220
GTMø160/50	160	50	3.0	1220
GTMø180/58	180	58	3.5	1220
GTMø200/65	200	65	3.5	1220

Special size, cut pieces are available on request.

