

# HTK150

## Heavy wall adhesive-lined polyolefin tubing

150°C耐高溫、磨擦熱收縮套管



normal size		as supplied inside diameter	after recovered inside diameter	after recovered wall thickness	style*	standard length
(mm)	(inch)	(min.)(mm)	(max.)(mm)	(min.)(mm)		(m/spool)
3/64	1.2	1.2	0.6	0.25±0.04	0	200
1/16	1.6	1.6	0.8	0.25±0.04	0	200
3/32	2.4	2.4	1.2	0.25±0.04	0	200
1/8	3.2	3.2	1.6	0.25±0.04	0	100
3/16	4.8	4.8	2.4	0.25±0.04	0	100
1/4	6.4	6.4	3.2	0.30±0.05	0	100
3/8	9.5	9.5	4.8	0.30±0.05	-	50
1/2	12.7	12.7	6.4	0.30±0.05	-	50
3/4	19.1	19.1	9.5	0.43±0.07	-	50
1	25.4	25.4	12.7	0.48±0.07	-	50
1 1/2	38.1	38.1	19	0.51±0.07	-	50

\* 0=airfilled or oval

- =flattened

## HTK150 150°C high performance, thin wall flexible PVDF tubing

### Applications

Special purpose for high-temperature, abrasion and cut-tough resistance or superior chemical and solvent resistant properties.

Clear tube applies to protect wire and cable markers for providing full inspect ability of each item covered.

### Characteristics

Excellent flame resistance

High temperature performance

Thinner walls than most general purpose polyolefin tubes.

### Operating temperature range

Operating temperature: -55°C ~ 150°C

Minimum full recovery temperature: 135°C

### Approvals / Specifications

Meet SAE-AMS-DTL-23053/8